

Stingray Portable Level-Velocity Logger

Model

STINGRAY

Approximate shipping weight: 10 lbs / 4.5 kg

STANDARD FEATURES:

- QZ02 submersible ultrasonic Level-Velocity Sensor
- sensor cable 25 ft / 7.6 m shielded tri-coaxial
- sensor mounting bracket stainless steel
- enclosure Watertight, airtight, dust proof (IP 67) polycarbonate
- display LCD bargraph for level, velocity, temperature, logger and battery capacity
- power 4 Alkaline D-cell batteries
- output RS232, 28,800 Baud
- data logger 130,000 data point capacity (512K)
- Greyline Logger' PC software for Windows™
- RS232 cable with DB9 M/F connectors
- 1 Manual Installation and Operation

OPTIONS AND ACCESSORIES

QTY	CODE	DESCRIPTION
	PVXC5	Sensor Cable Extension 50 ft / 15 m with watertight connectors
	QZ02-UT-01-PS	Spare/replacement Sensor with 25' (7.6 m) cable
	RENT	Monthly rental (* Requires purchase of QZ02 sensor)
	MNL	Additional Manuals (One supplied with each unit)
	VSJ6	SS Pipe Mounting Band for 6"/150 mm ID pipes (fits ±0.5"/13 mm)
	VSJ8	SS Pipe Mounting Band for 8"/200 mm ID pipes (fits ±0.5"/13 mm)
	VSJ10	SS Pipe Mounting Band for 10"/250 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ12	SS Pipe Mounting Band for 12"/300 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ14	SS Pipe Mounting Band for 14"/350 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ15	SS Pipe Mounting Band for 15"/375 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ16	SS Pipe Mounting Band for 16"/400 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ18	SS Pipe Mounting Band for 18"/450 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ20	SS Pipe Mounting Band for 20"/500 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ24	SS Pipe Mounting Band for 24"/600 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ30	SS Pipe Mounting Band for 30"/750 mm ID pipes (adjustable ±0.5"/13 mm)
	VSJ32-40	SS Half-Pipe Mounting Band for 32-40"/800-1000 mm ID pipes
	VSJ42-54	SS Half-Pipe Mounting Band for 42-54"/1100-1375 mm ID pipes
	VSJ56-72	SS Half-Pipe Mounting Band for 56-72"/1400-1800 mm ID pipes

Effective: 1-Mar-05